



TECHNICAL DATA SHEET: WOODPLUS - STABILIZER

Page 1 of 2

DESCRIPTION

WoodPlus Stabilizer is a 100% acrylic, colorless, low solids product designed to protect new wood surfaces during the first 3-6 months of exposure. **Stabilizer** allows the wood to properly dry out, while helping to minimize splitting and cracking. **Stabilizer** is a non hazardous and ecologically sound product with a minimal VOC content (3.6 g/L). It is formulated with special UV blockers and water repellants to reduce the effects of sunlight and water penetration. **WoodPlus Stabilizer** is also recommended for use as a "primer" on new wood, brick, cement, concrete or stucco surfaces on which you plan to apply **WoodPlus Opaque 20**.

RECOMMENDED USES

WoodPlus Stabilizer can be used on all exterior wood substrates, decking, siding, log homes, shakes and shingles. **Stabilizer** is particularly effective on Pressure Treated (PT) wood and cedar. **IMPORTANT: WoodPlus Stabilizer** also acts as a primer on new wood, brick, cement, concrete or stucco surfaces on which you plan to apply **WoodPlus Opaque 20**.

PREPARATION

We recommend that you lightly power wash the surface to remove dirt, grease, oil or other contamination. Cover surface areas not to be sprayed (such as windows) before proceeding with the application.

PRODUCT CHARACTERISTICS

- Excellent protection against UV rays and discoloration
- Excellent barrier from the elements, mold, mildew
- 100% Acrylic
- No solvents
- Extremely low VOC level (3.6 g/L)
- Tintable (using Universal colorants)
- Safe and easy to apply - Odorless
- Dries quickly (1-2 hours)
- Minimizes splitting and cracking
- Breathable finish
- Soap & Water clean-up
- Rapid recoat (1 -2 hrs)

APPLICATION

Product is ready to use. Do not dilute. Best applied with a low volume sprayer or garden pump sprayer. Saturate the surface (brushing or rolling out the excess). Wait about 1-2 hours before applying a second coat. Exercise caution when spraying in windy conditions.

MAINTENANCE

Can be re-applied as needed. Before applying maintenance coat, we recommend that you lightly power wash the surface to remove dirt, grease, oil or other contamination. Cover areas not to be coated.

TECHNICAL DATA

Colour:	White liquid (colorless when dry)	Flashpoint:	N/A
Odor:	Slight ammonia	VOC Content:	3.6 g/L coating
Solids:	10%	Gloss level:	15 G.U.
Wt/gallon:	8.5 lb/gal		

WoodPlus Coatings
12-1064 Salk Road, Ste. 233; Pickering, ON Canada L1W 4B5
Tel.: 416-399-5067 • Fax: 905-421-0151
Website: www.woodpluscoatings.com Email: sales@woodpluscoatings.com

Updated: 09/12/09



TECHNICAL DATA SHEET: WOODPLUS - STABILIZER

Page 2 of 2

WOODPLUS – STABILIZER (continued...)

COVERAGE *

Smooth surface (wood):	400-500 sq ft/US gal (40-50m ² /3.78L)
Rough surface (wood):	200-250 sq ft/US gal (20-25m ² /3.78L)
Brick, interlocking stones:	150-200 sq ft/US gal (15-20m ² /3.78L)
Concrete & cement:	200-250 sq ft/US gal (20-25m ² /3.78L)
Concrete blocks:	100-150 sq ft/US gal (10-15m ² /3.78L)
Stucco:	150-200 sq ft/US gal (15-20m ² /3.78L)

* **NOTE:** The above coverage is approximate and may vary due to the porosity of the surface. When applying a second coat on brick, cement, concrete or stucco surfaces, add 50% to the suggested coverage dimensions above.

DRY TIME

Touch (1—2 hrs); Recoat (2—3 hrs); Light traffic (24 hrs)

CLEAN-UP

Use soap and water to clean-up equipment.

AVAILABLE COLOURS

White liquid (colorless when dry) – Tintable using Universal colorants - maximum colorant = 1 ounce/gal

AVAILABLE CONTAINER SIZES

1 gallon (3.78L), 5 gallon (18.79L), Drums (200L), Totes (1000L)

WARRANTY: WoodPlus warrants the quality of its products. They are in conformity with the description provided in the technical data sheets and on the labels for which they are intended, as indicated by the company. Since the manufacturer has no control over the circumstances, the methods and the conditions appropriate to their intended uses, this warranty applies only to the high quality of WoodPlus products. If you are not satisfied with the performance of this product after applying according to the manufacturer's instructions on the product label, WoodPlus will replace the product or refund the purchase price at its discretion. Proof of purchase, complaint description, and photograph required. Manufacturer's liability is limited to refund of purchase price or product replacement. In no event shall WoodPlus be responsible for labour, personal injury, or damage. THERE ARE NO OTHER EXPRESS WARRANTIES. IN NO EVENT SHALL WOODPLUS BE LIABLE FOR INCIDENTAL OR CONSEQUENTIAL DAMAGES RESULTING FROM ANY BREACH OF THIS WARRANTY OR ANY IMPLIED WARRANTY OF MERCHANTABILITY AND FITNESS FOR USE.

WoodPlus Coatings
12-1064 Salk Road, Ste. 233; Pickering, ON Canada L1W 4B5
Tel.: 416-399-5067 • Fax: 905-421-0151
Website: www.woodpluscoatings.com Email: sales@woodpluscoatings.com

Updated: 09/12/09