



# WoodPlus Special UV

Exterior Translucent Coating  
Teinture translucide pour extérieur

WoodPlus  
sales@woodpluscoatings.com  
www.woodpluscoatings.com



**PROJECT DESCRIPTION:** A 10 year old pool deck with lots of horizontal surface (prone to mildew). The previous homeowner became disenchanted with the wood coating utilized so every couple of years they sanded the entire deck area down to bare wood and recoated the surface with an alkyd stain.

**PREP'N:** the surface was treated with a mold control product applied with a garden sprayer. Although the product is advertised to work in 30 sec's, we gave it triple that amount of time and utilized a bristle brush to get at the truly "tough stuff". Where mold was particularly heavy, we went over it a second time. As completed, each area was washed down with a garden hose (spray nozzle). The wood was very lightly sanded to remove "feathers" on the surface, sanding dust was diligently vacuumed, & the wood was allowed to dry completely. Finally, plants were protected with scrap wood or cardboard.



Step #1

**STEP #1:** the cans were mixed to ensure consistent colour, then, working to avoid direct sunlight, edges were "cut-in";

**STEP #2:** applied on two boards at a time keeping a "wet edge" (doing the length to avoid lap marks), then, working towards the exit, the single coat of WP Special UV Chamois is applied with a good quality nylon polyester brush; then,

**STEP #3:** again avoiding direct sunlight (allowing approx. 2 hrs. to dry), a 2nd coat applied (note in the final collage below that the retaining wall was finished with WP Opaque 20—Pecan);



Step #2



Step #3

