



Technical Data Sheet

WoodPlus – Stabilizer (Feb.14'10)

WoodPlus
sales@woodpluscoatings.com
www.woodpluscoatings.com

DESCRIPTION

WoodPlus Stabilizer is an 100% acrylic, colorless, low solids product designed to protect new wood surfaces during the first 3-6 months of exposure. Stabilizer allows the wood to properly dry out, while helping to minimize splitting and cracking. Stabilizer is a non hazardous, **low emissions (low VOC's)** product. It is formulated with special water repellants to reduce the effects of sunlight and water penetration. **WoodPlus Stabilizer** is also recommended for use as a “primer” on new wood, brick, cement, concrete or stucco surfaces on which you plan to apply WoodPlus Opaque 20.

RECOMMENDED USES

WoodPlus Stabilizer can be used on all exterior wood substrates, decking, siding, log homes, shakes and shingles. **Stabilizer** is particularly effective on Pressure Treated (PT) wood and cedar. **IMPORTANT: WoodPlus Stabilizer** also acts as a primer on new wood, brick, cement, concrete or stucco surfaces on which you plan to apply WoodPlus Opaque 20.

PRODUCT CHARACTERISTICS

- Excellent protection against discoloration
- Excellent barrier from the elements, mold, mildew
- 100% Acrylic
- No solvents
- **Low emissions (low VOC's)**
- Tintable (using Universal colorants)
- Safe and easy to apply - Odorless
- Dries quickly (1-2 hours)
- Minimizes splitting and cracking
- Breathable finish
- Soap & Water clean-up
- Rapid recoat (1 –2 hrs)

PREPARATION

We recommend that you lightly power wash the surface to remove dirt, grease, oil or other contamination. Cover surface areas not to be sprayed (such as windows) before proceeding with the application.

APPLICATION

Product is ready to use. Do not dilute. Best applied with a low volume sprayer or garden pump sprayer. Saturate the surface (brushing or rolling out the excess). Wait about 1-2 hours before applying a second coat. Exercise caution when spraying in windy conditions.

MAINTENANCE

Can be re-applied as needed. Before applying maintenance coat, we recommend that you lightly power wash the surface to remove dirt, grease, oil or other contamination. Cover areas not to be coated. When used on roof shingles, re-apply annually to continue protection against mold, mildew, and discoloration.

TECHNICAL DATA

Colour:	White liquid (colorless when dry)	Flashpoint :	N/A
Odor:	Slight ammonia	VOC Content :	Depending on Region *
Solids :	10%	Gloss Level :	15 GU
Wt./gal :	8.5 lb/gal		

VOC's *	North America	E.U.	Australia	Asia
Stabilizer	15 gms/L	<5 gms/L	< 5 gms/L	< 5 gms/L

COVERAGE *

Smooth surface (wood):	400-500 sq ft/US gal (40-50m ² /3.78L)
Rough surface (wood):	200-250 sq ft/US gal (20-25m ² /3.78L)
Brick, interlocking stones:	150-200 sq ft/US gal (15-20m ² /3.78L)
Concrete & cement:	200-250 sq ft/US gal (20-25m ² /3.78L)
Concrete blocks:	100-150 sq ft/US gal (10-15m ² /3.78L)
Stucco:	150-200 sq ft/US gal (15-20m ² /3.78L)

* NOTE: The above coverage is approximate and may vary due to the porosity of the surface. When applying a second coat on brick, cement, concrete or stucco surfaces, add 50% to the suggested coverage dimensions above.



Technical Data Sheet

WoodPlus – Stabilizer (Feb.14'10)

WoodPlus
sales@woodpluscoatings.com
www.woodpluscoatings.com

DRY TIME: Touch (1 hour) – Recoat (2-3 hours) – Light traffic (24 hours)

CLEAN-UP: Use soap and water to clean-up equipment.

AVAILABLE COLOURS

White liquid (colorless when dry) – Tintable using Universal colorants (factory tinting available on request);

AVAILABLE CONTAINER SIZES *

1 gallon (3.78L), 5 gallon (18.79L)

*Drums (200L) and Totes (1000L) industrial only...

CUSTOMER SATISFACTION GUARANTEE (Please visit the warranty page on our website for current details.):

WoodPlus warrants the quality of its products. They are in conformity with the description provided in the technical data sheets and on the labels for which they are intended, as indicated by the company. Since the manufacturer has no control over the circumstances, the methods and the conditions appropriate to their intended uses, this guarantee applies only to the high quality of WoodPlus products. If you are not satisfied with the performance of this product after applying according to the details in our Application Guide, WoodPlus will replace the product or refund the purchase price at our discretion. Proof of purchase, complaint description, and photograph required. Manufacturer's liability is limited to refund of purchase price or product replacement. In no event shall WoodPlus be responsible for labour, personal injury, or damage. **THERE ARE NO OTHER EXPRESS WARRANTIES. IN NO EVENT SHALL WOODPLUS BE LIABLE FOR INCIDENTAL OR CONSEQUENTIAL DAMAGES RESULTING FROM ANY BREACH OF THIS WARRANTY OR ANY IMPLIED WARRANTY OF MERCHANTABILITY AND FITNESS FOR USE.**