



# Technical Data Sheet

## WoodPlus – Waterproofer (Feb.14'10)

WoodPlus  
[sales@woodpluscoatings.com](mailto:sales@woodpluscoatings.com)  
[www.woodpluscoatings.com](http://www.woodpluscoatings.com)

### DESCRIPTION

WoodPlus Waterproofer is a 100% Acrylic, colorless, low film forming product designed to protect interior or exterior concrete, cement, and brick surfaces. Waterproofer does not contain any solvents. It is an ecologically sound product with low emissions (low VOC's). Waterproofer contains special UV blockers and water repellants to reduce the effects of sunlight and water penetration.

### RECOMMENDED USES

WoodPlus Waterproofer can be used on all interior or exterior concrete, cement, and brick surfaces including: interlocking stones, concrete garage or basement floors and walkways, patio stones, concrete blocks, and stucco. IMPORTANT: If you plan to apply WoodPlus Opaque 20 on your brick, cement, concrete or stucco project, we recommend that you use WoodPlus Stabilizer as a primer instead of WoodPlus Waterproofer.

### PRODUCT CHARACTERISTICS

- Excellent protection for concrete, cement, & brick surfaces
- Excellent protection against UV rays & discoloration
- Excellent barrier from the elements, mold, mildew
- Safe & easy to use - Odorless
- 100% Acrylic
- Breathable finish
- No solvents
- Extremely low emissions
- Tintable (Dries quickly (1 – 2 hrs))

### PREPARATION

We recommend that you lightly power wash the surface to remove dirt, grease, oil or other contaminations. Cover surface areas not to be sprayed (such as windows) before proceeding with the application.

### APPLICATION

Product is ready to use. Do not dilute. Best applied with a low volume sprayer or garden pump sprayer. Saturate the surface (brushing or rolling out the excess). Wait about 1-2 hours before applying a second coat. Exercise caution when spraying in windy conditions.

### MAINTENANCE

Can be re-applied as needed. Before applying maintenance coat, we recommend that you lightly power wash the surface to remove dirt, grease, oil or other contamination. Cover areas not to be coated.

### TECHNICAL DATA

- Colour: White liquid (colorless when dry)
- Odor: Slight ammonia
- Solids: 10%
- Wt/gallon: 8.5 lb/gal
- Flashpoint: N/A
- VOC Content \*: *Dependent on region*
- Gloss level: 15 G.U. (2 coats)
- Viscosity: 250 cpu
- Water Permeability: Meets U.S. Federal Spec. T-P-0035
- Water Permeance of Masonry: Meets ASTM E-514-74
- Moisture Vapour Transmission: Meets ASTM D-1653

VOC's *	North America	E.U.	Australia	Asia
Waterproofer	3.6 gms/L	<5 gms/L	< 5 gms/L	< 5 gms/L

### COVERAGE \*

The suggested coverage below is approximate and could vary based on surface porosity:

Brick, interlocking stones: .....150-200 sq ft/US gal (15-20m<sup>2</sup>/3.78L)

Concrete & cement: .....200-250 sq ft/US gal (20-25m<sup>2</sup>/3.78L)

Concrete blocks:.....100-150 sq ft/US gal (10-15m<sup>2</sup>/3.78L)

Stucco:.....150-200 sq ft/US gal (15-20m<sup>2</sup>/3.78L)

\* NOTE: For the second coat, add 50% to the suggested coverage dimensions above.

**DRY TIME:** Touch (1-2 hour) – Recoat (2-3 hours) – Light traffic (24 hours)

**CLEAN-UP:** Use soap and water to clean-up equipment.



# Technical Data Sheet

## WoodPlus – Waterproofer (Feb.14'10)

**WoodPlus**  
[sales@woodpluscoatings.com](mailto:sales@woodpluscoatings.com)  
[www.woodpluscoatings.com](http://www.woodpluscoatings.com)

### AVAILABLE COLOURS

White liquid (colorless when dry) – Tintable using Universal colorants - maximum colorant = 1 ounce/gal

### AVAILABLE CONTAINER SIZES\*

1 gallon (3.78L), 5 gallon (18.79L)

\*Drums (200L) and Totes (1000L) industrial only.

**CUSTOMER SATISFACTION GUARANTEE** (Please visit the warranty page on our website for current details.):

WoodPlus warrants the quality of its products. They are in conformity with the description provided in the technical data sheets and on the labels for which they are intended, as indicated by the company. Since the manufacturer has no control over the circumstances, the methods and the conditions appropriate to their intended uses, this guarantee applies only to the high quality of WoodPlus products. If you are not satisfied with the performance of this product after applying according to the details in our Application Guide, WoodPlus will replace the product or refund the purchase price at our discretion. Proof of purchase, complaint description, and photograph required. Manufacturer's liability is limited to refund of purchase price or product replacement. In no event shall WoodPlus be responsible for labour, personal injury, or damage. **THERE ARE NO OTHER EXPRESS WARRANTIES. IN NO EVENT SHALL WOODPLUS BE LIABLE FOR INCIDENTAL OR CONSEQUENTIAL DAMAGES RESULTING FROM ANY BREACH OF THIS WARRANTY OR ANY IMPLIED WARRANTY OF MERCHANTABILITY AND FITNESS FOR USE ..**