



ULTRA10™

Translucent Wood Coating
100% acrylic – Exterior / Interior

DESCRIPTION

WoodPlus™ Ultra10™ is a 100% acrylic high film-forming translucent coating designed for use on **exterior and interior wood surfaces**.

Ultra10™ is a non-hazardous and low emissions (< 10g/L VOC) product that contains NO solvents. The translucent finish provides for full wood grain visibility and is specially formulated to provide optimal UV protection. Ultra10™ provides a very breathable film that provides an exceptional barrier against excess moisture uptake from the elements.

TECHNICAL DATA

Colour: Opaque liquid	Flashpoint: N/A.
Odour: Mild ammonia	VOC content: < 10 g/L
Solids: 25 +/- 1% by weight	Gloss level: 27 G.U. (2 coats)
Weight/gal: 10.48 lb/gal	Viscosity: 600 cpu

RECOMMENDED USES

Wood siding, log homes.

Exterior and interior wood surfaces including sheds, gazebos, park benches and garden furniture.




Ultra10's clear base must be tinted for exterior use. The clear base can be used for interior application or as a top coat for exterior wood surfaces already tinted.

PRODUCT CHARACTERISTICS







- Designed for high performance in any climate
- Outstanding UV protection
- Excellent physical wear characteristics
- Self-priming, water reducible
- Easy application, quick drying
- Excellent water repellency
- Superior adhesion
- Excellent colour & gloss retention
- Breathable finish
- Simple maintenance: clean with soap and warm water.

AVAILABLE COLOURS (Base: Clear 000 or 100 Natural for retail stores)

 000 Clear Satin	 100 Natural	 200 Cedar	 275 Honey Gold	 300 Oak	 350 Chamois
 400 Walnut	 425 TMW Brown	 430 Espresso	 450 DK Walnut	 480 Woodsmoke	 490 HK Brown
 500 Teak	 600 Mahogany	 825 Sky Grey	 850 Barn Board		

Special colours

Contact Woodplus
for information

 853 Green	 867 Bleu Jay	 869 Red	 871 Yellow	 908 Black
--	---	--	---	--

WOODPLUS

ECO WOOD PROTECTION

ULTRA10™

Translucent Wood Coating
100% acrylic – Exterior / Interior



COVERAGE

Type de wood surface	First Coat	Second Coat
Smooth surface	300-400 ft ² /gal (30-40 m ² /3.78 L)	400-500 ft ² /gal (40-50 m ² /3.78 L)
Rough/textured surface	200-300 ft ² /gal (20-30 m ² /3.78 L)	300-400 ft ² /gal (30-40 m ² /3.78 L)

Note: The above coverage is approximate and may vary due to surface porosity of the substrate.

SURFACE PREPARATION INSTRUCTIONS

- Surfaces must be clean and dry (for wood: less than 19% moisture content).
- Remove all traces of dirt, wax, grease, mildew, etc.
- Do not apply over varnishes and urethanes.
- New smooth wood must be sanded with 60-80 grit sandpaper to remove mill glaze.
- Remove all sanding dust with clean rags and acetone prior to application.

APPLICATION INSTRUCTIONS

TWO COATS (2-4 hours between coats)

- Product is ready to use. Do not thin.
- Stir thoroughly before and during use.
- DO NOT apply in direct sunlight or on a surface that is hot to the touch.
- Temperature must be above 10°C and not more than 30°C.
- Apply in the direction of the grain completing a full board at a time.
- DO NOT apply in wet weather or when inclement weather is imminent.
- Maintain a wet edge and saturate any open or cut end boards.

CLEANUP

Clean equipment with warm soapy water immediately after use.

DRY TIME

- To the touch (1 hour)
- Recoat (2-4 hours)

AVAILABLE CONTAINER SIZES

- 1 gallon (3.78 L), 5 gallons (18.79 L)
- *Barrels (200 L) and Totes (1 000 L)
*Industry only

MAINTENANCE

Clean surfaces regularly: thorough cleaning with garden hose/sprayer to remove dirt, debris, and effects of weather on the coating. DO NOT use chemical strippers/cleaners to clean surfaces before coating. Inspect surfaces on a regular basis to identify damaged areas (wood cracks, splits, loose or rotten boards, etc.) and repair them quickly to prevent further deterioration. Apply maintenance or touch-up coats as required.

WARRANTY

This product will give full satisfaction if applied according to the manufacturer's instructions. Manufacturer's liability is limited to the replacement of the product and does not include manpower if found defective upon inspection.



woodpluscoatings.com
admin@woodcoatings.com
Toll free: 1-844-373-9663