



TECHNICAL DATA SHEET ULTRA 10

WoodPlus Coatings Group Ltd.
13 Holland Drive, Unit 10B
Bolton, Ontario, Canada L7E 1G4
Bus.: (905) 857-2227
Toll free: 1-844-373-9663



DESCRIPTION

WoodPlus™ Ultra 10 is a 100% acrylic translucent coating designed for use on exterior and interior vertical wood surfaces. Ultra 10 is a non-hazardous and low emissions (9.6 g/L VOC) product that contains NO solvents. The translucent finish provides for full wood grain visibility and is specially formulated to provide optimal UV protection. Ultra 10 provides a very breathable film that provides an exceptional barrier against excess moisture uptake from the elements.

RECOMMENDED USES

Wood siding, log homes and vertical surfaces. Exterior and interior wood surfaces including siding, log homes, sheds, park benches, garden furniture, etc. Ultra 10's clear bases must be tinted for exterior use. However, the clear bases can be used for interior application or as a top coat for exterior wood surfaces already tinted.

IMPORTANT: FOR USE ON DECKING, PLEASE CONTACT YOUR LOCAL SUPPLIER FOR SPECIFIC APPLICATION INSTRUCTIONS.

AVAILABLE COLOURS – (2 bases: Clear 000 and Natural 100) + Standard colours below)

Regular Wood Colours
Couleurs pour bois ordinaire

100 - Natural / Naturel	200 - Cedar / Cèdre	275 - Honey Gold / Miel doré
300 - Oak / Chêne	350 - Chamolis	400 - Walnut / Noyer
425 - TMW Brown / Brun TMW	430 - Espresso	450 - Dark Walnut / Noyer sombre
480 - Woodsmoke / Fumée de bois semi-opaque	490 - HK Brown / HK brun	500 - Teak / Teck
600 - Mahogany / Acajou	825 - Sky Grey / Ciel Gris	850 - Barnboard / Bois de grange semi-opaque

EXTERIOR/INTERIOR USES: decks, fences, log siding, beams, wood crown moulding, wood siding, hot tub skirts, garden furniture. The special design also permits application on an array of substrates such as cedar, shakes, shingles, T1-11, trim boards, primed fiber cement board, torrefied wood & pressure-treated wood.

See your paint dealer for complete colour samples.

NOTE: Care has been taken to ensure the accuracy of sample chips but slight variations can occur. Colours as shown may vary from actual product colours. Always perform a test to confirm the colour result. Final colour may vary depending on the wood, wood colour, grain, and texture.



Colours for Dark Torrefied Wood
Couleurs pour bois torréfié foncé

Unfinished Dark wood / Bois nu foncé	430 - Espresso / Espresso	400 - Walnut / Noyer
425 - TMW Brown / TMW Brun	600 - Mahogany / Acajou	450 - Dark Walnut / Noyer sombre

Colours for Light Torrefied Wood
Couleurs pour bois torréfié pâle

Unfinished Light wood / Bois nu pâle	430 - Espresso / Espresso	400 - Walnut / Noyer
425 - TMW Brown / TMW Brun	600 - Mahogany / Acajou	450 - Dark Walnut / Noyer sombre

USAGE EXTÉRIEUR ET INTÉRIEUR : terrasses, clôtures, lambris de bois rond, poutres, moulure couronnée en bois, parements en bois, jupe de spa, meubles de jardin. Ultra 10 est également formulé pour application sur une foule de subjectiles : bois d'œuvre, parements, bardeaux, T1-11, moulures, panneaux de fibrociment apprêtés, bois traité sous pression, bois torréfié.

Éventail de couleurs disponible chez votre marchand de peinture.

NOTE : Les échantillons de couleur sont approximatifs. Effectuez toujours un essai pour vous assurer d'obtenir la teinte désirée. La couleur finale pourrait varier suivant le type de bois que vous utilisez, sa teinte naturelle, son grain et sa texture.




SPECIAL FACTORY-MADE TRANSLUCENT COLOURS

908 - Black	867 - Blue Jay	853 - Green	869 - Red	871 - Yellow

PRODUCT CHARACTERISTICS

- Designed for high performance in any climate
- Outstanding UV protection
- Excellent physical wear characteristics
- Self priming, water reducible
- Easy application, fast drying
- Excellent water repellency
- Superior adhesion
- Excellent colour & gloss retention
- Breathable finish
- Easy maintenance – soap and water cleanup
- Clear and natural bases tintable with universal colorants



TECHNICAL DATA SHEET ULTRA 10

WoodPlus Coatings Group Ltd.
13 Holland Drive, Unit 10B
Bolton, Ontario, Canada L7E 1G4
Bus.: (905) 857-2227
Toll free: 1-844-373-9663



TECHNICAL DATA

Colour:	Opaque liquid	Flashpoint:	90°C
Odour:	Mild ammonia	VOC content:	9.6 g/L
Solids:	25 +/- 1% by weight	Gloss level:	27 G.U. (2 coats)
Weight/gal:	10.48 lb/gal	Viscosity:	600 cpu

SURFACE PREPARATION INSTRUCTIONS

- Wood must be clean and dry (less than 19% moisture content for new natural wood, less than 5% moisture content for torrefied wood).
- Remove all traces of dirt, wax, grease, mildew, etc.
- Do not apply over varnishes and urethanes.
- New smooth wood must be sanded with 60-80 grit sandpaper to remove mill glaze.
- Remove all sanding dust with clean rags and acetone prior to application.

APPLICATION INSTRUCTIONS (For more information, scan the QR code below or go to: www.woodpluscoatings.com .)

- Product is ready to use. Do not thin.
- Stir thoroughly before and during use.
- DO NOT apply in direct sunlight or on a surface that is hot to the touch.
- Temperature must be above 10°C and not more than 30°C.
- Apply in the direction of the grain completing a full board at a time.
- Maintain a wet edge and saturate any open or cut end boards.
- DO NOT apply in wet weather or when inclement weather is imminent.

COVERAGE

Type of wood surface	First coat	Second Coat
Smooth surface	300-400 ft ² /gal (30-40 m ² /3.78L)	400-500 ft ² /gal (40-50 m ² /3.78L)
Rough/textured surface	200-300 ft ² /gal (20-30 m ² /3.78L)	300-400 ft ² /gal (30-40 m ² /3.78L)

Note: The above coverage is approximate and may vary due to surface porosity of the substrate.

CLEANUP: Soap and water

DRY TIME: To the touch (1 hour) – **Recoat** (3-4 hours)

AVAILABLE CONTAINER SIZES

1 gallon (3.78L), 5 gallons (18.79L)

*Drums (200L) and Totes (1000L) industrial only.

MAINTENANCE

Clean surfaces regularly: thorough cleaning with garden hose/sprayer to remove dirt, debris, and effects of weather on the coating. DO NOT use chemical strippers/cleaners to clean surfaces before coating. Inspect surfaces on a regular basis to identify damaged areas (wood cracks, splits, loose or rotten boards, etc.) and repair them quickly to prevent further deterioration. Apply maintenance or touch-up coats as required.

WARRANTY

This product will give full satisfaction if applied according to the manufacturer's instructions. Manufacturer's liability is limited to the replacement of the product and does not include manpower if found defective upon inspection.



Scan QR code
to access
detailed