



TECHNICAL DATA SHEET ULTRA 10

WoodPlus Coatings Group Ltd.
12-1064 Salk Rd., Suite 233
Pickering, Ontario, Canada L1W 4B5
Bus.: 1-844-373-9663



DESCRIPTION

WoodPlus™ Ultra 10 is a 100% acrylic high film-forming translucent coating designed for use on exterior and interior vertical wood surfaces. Ultra 10 is a non-hazardous and low emissions (< 10g/L VOC) product that contains NO solvents. The translucent finish provides for full wood grain visibility and is specially formulated to provide optimal UV protection. Ultra 10 provides a very breathable film that provides an exceptional barrier against excess moisture uptake from the elements.

RECOMMENDED USES

Wood siding, log homes and vertical surfaces. Exterior and interior wood surfaces including siding, log homes, sheds, park benches, garden furniture, etc. Ultra 10's clear bases must be tinted for exterior use. However, the clear bases can be used for interior application or as a top coat for exterior wood surfaces already tinted.

IMPORTANT: NOT RECOMMENDED FOR USE ON DECK FLOORS OR OTHER HORIZONTAL SURFACES.

AVAILABLE COLOURS – (2 bases: Clear 000 and Natural 100) + Standard colours below)



000 Clear Satin / Satin clair



100 Natural / Naturel



200 Cedar / Cèdre



275 Honey Gold / Miel doré



300 Oak / Chêne



350 Chamois



400 Walnut/ Noyer




425 TMW Brown / Brun TMW




430 Espresso



450 DK Walnut / Noyer sombre



480 Woodsmoke / Fumée de bois



490 HK Brown / Brun HK



500 Teak / Teck



600 Mahogany / Acajou



825 Sky Grey / Gris ciel



850 Barn Board / Bois de grange

Special Translucent Colours: Contact WoodPlus for information

Couleurs spéciales : Contacter WoodPlus pour plus d'information



853 Green / Vert



867 Blue Jay / Geai bleu



869 Red / Rouge



871 Yellow / Jaune



908 Black / Noir

PRODUCT CHARACTERISTICS

- Designed for high performance in any climate
- Outstanding UV protection
- Excellent physical wear characteristics
- Self priming, water reducible
- Easy application, quick drying
- Excellent water repellency
- Superior adhesion
- Excellent colour & gloss retention
- Breathable finish



TECHNICAL DATA SHEET ULTRA 10

WoodPlus Coatings Group Ltd.
12-1064 Salk Rd., Suite 233
Pickering, Ontario, Canada L1W 4B5
Bus.: 1-844-373-9663



TECHNICAL DATA

Colour:	Opaque liquid	Flashpoint:	N/A
Odour:	Mild ammonia	VOC content:	< 10g/L
Solids:	25 +/- 1% by weight	Gloss level:	27 G.U. (2 coats)
Weight/gal:	10.48 lb/gal	Viscosity:	600 cpu

SURFACE PREPARATION INSTRUCTIONS

- Wood must be clean and dry (less than 19% moisture content for new natural wood, less than 5% moisture content for torrefied wood).
- Remove all traces of dirt, wax, grease, mildew, etc.
- Do not apply over varnishes and urethanes.
- New smooth wood must be sanded with 60-80 grit sandpaper to remove mill glaze.
- Remove all sanding dust with clean rags and acetone prior to application.

APPLICATION INSTRUCTIONS (For more information, scan the QR code below or go to: www.woodpluscoatings.com .)

- Product is ready to use. Do not thin.
- Stir thoroughly before and during use.
- DO NOT apply in direct sunlight or on a surface that is hot to the touch.
- Temperature must be above 10°C and not more than 30°C.
- Apply in the direction of the grain completing a full board at a time.
- Maintain a wet edge and saturate any open or cut end boards.
- DO NOT apply in wet weather or when inclement weather is imminent.

COVERAGE

Type of wood surface	First coat	Second Coat
Smooth surface	300-400 ft ² /gal (30-40 m ² /3.78L)	400-500 ft ² /gal (40-50 m ² /3.78L)
Rough/textured surface	200-300 ft ² /gal (20-30 m ² /3.78L)	300-400 ft ² /gal (30-40 m ² /3.78L)

Note: The above coverage is approximate and may vary due to surface porosity of the substrate.

CLEANUP: Warm water

DRY TIME: To the touch (1 hour) – **Recoat** (2-4 hours)

AVAILABLE CONTAINER SIZES

1 gallon (3.78L), 5 gallons (18.79L)

*Drums (200L) and Totes (1000L) industrial only.

MAINTENANCE

Clean surfaces regularly: thorough cleaning with garden hose/sprayer to remove dirt, debris, and effects of weather on the coating. DO NOT use chemical strippers/cleaners to clean surfaces before coating. Inspect surfaces on a regular basis to identify damaged areas (wood cracks, splits, loose or rotten boards, etc.) and repair them quickly to prevent further deterioration. Apply maintenance or touch-up coats as required.

WARRANTY

This product will give full satisfaction if applied according to the manufacturer’s instructions. Manufacturer’s liability is limited to the replacement of the product and does not include manpower if found defective upon inspection.